

Tractors and farm equipment limited, plot.no-6, savakarnagar, IDA nacharam, 'X roads, hyderabad-500076, phone : 040-32510456/457/458, fax:040-27184631,rajanandan.m@tafe.com, 8790843875

Sl.No	Approved Model	Specifications	ENGINE /PTO HP	PTO HP	DRIVE	Sale price including Corporation service charges and GST@12%
1	2		3	4	5	
1	TAFE MF 1035 R SDDDB DC	Engine HP :35, Make:SIMPSONS S324 TIII A, Cylinders:3, Cubic Capacity (cc):2400, Fuel injection pump:Inline,Clutch Type:Dual, TTransmission ype:Sliding mesh, "Number of speeds:8 Forward + 2 Reverse, ""Tyres Dimensions:6.00 x 16 Front 12.4 x 28 Rear ,Minimum turning circle radius with rakes (mm):2800, PTO Type:Live, single speed PTO, PTO Speed:540 RPM @ 1650 ERPM, "Hydraulics Lifting capacity(Lower links at horizontal position):1100 kgf, "Brakes Type:Dry disc brakes (SDDDB), Steering Type:Manual steering, Overall length (mm):3120, Overall width (mm):1675, Overall height (mm):2185, Wheel base (mm):1830, Ground clearance (mm):340, Total weight (kg):1713, Fuel tank capacity (L):47,	36.5/35.1	35.1	2 WD	523720
2	Massey Ferguson MF 1035 DI , SC. DURA BREAK 8+2, R Tractor	Engine HP :35, Make:SIMPSONS S324 TIII A, Cylinders:3, Cubic Capacity (cc):2400, Fuel injection pump:Inline, Clutch Type:Single, Transmission ype:Sliding mesh, "Number of speeds:8 Forward + 2 Reverse, ""Tyres Dimensions:6.00 x 16 Front 12.4 x 28 Rear ,Minimum turning circle radius with brakes (mm):2800, PTO Type:Live, single speed PTO,PTO Speed:540 RPM @ 1650 ERPM, "Hydraulics Lifting capacity(Lower links at horizontal position):1100 kgf, "Brakes Type:Dry disc brakes (Dura Brakes), Steering Type:Manual steering, Overall length (mm):3120, Overall width (mm):1675, Overall height (mm):2185, Wheel base (mm):1830, Ground clearance (mm):340, Total weight (kg):1713, Fuel tank capacity (L):47,	36.5/35.1	35.1	2 WD	464720
3	TAFE MF 1035 SHAKTIS337	Engine HP :39, Make:SIMPSONS S337 T III A, Cylinders:3, Cubic Capacity (cc):2400, Fuel injection pump:Inline, Clutch Type:Dual dry , Transmission ype: Partial constant mesh, Number of speeds:8 Forward + 2 Reverse, Tyres Dimensions:6.00 x 16 Front13.6 x 28 Rear, " Minimum turning circle radius with brakes (mm):3200, PTO Type:Live, six splined shaft, PTO Speed:540 RPM @ 1500 ERPM, "Hydraulics Lifting capacity(Lower links at horizontal position):1100 kgf, "Brakes Type:Dry disc brakes (MDSS BRAKES), Steering Type:Manual steering , Overall length (mm):3340,Overall width mm):1650, Overall height (mm):2200, Wheel base (mm):1785, Ground clearance (mm):345, Total weight (kg):1750, Fuel tank capacity (L):47, "Additional features:Rear flat face with hitch railsOPK, "	37.5/35.8	35.8	2WD	537720

Sl.No	Approved Model	Specifications	ENGINE /PTO HP	PTO HP	DRIVE	Sale price including Corporation service charges and GST@12%
4	MF 1035 MAHASHKTI loadking	Engine HP :39, Make:SIMPSONS S337 T III A,Cylinders:3, Cubic Capacity (cc):2400, Fuel injection pump:Inline,Clutch Type:Dual dry, Transmission ype:PCM, Number of speeds:8 Forward + 2 Reverse, "Tyres Dimensions:6.00 x 16 Front13.6 x 28 Rear, "Minimum turning circle radius with brakes (mm):3200, PTO Type:Live, six splined shaft, PTO Speed:540 RPM @ 1500 ERPM, "Hydraulics Lifting capacity(Lower links at horizontal position):1100 kgf,Brakes Type:Dry disc brakes (Dura Brakes), Steering Type:Manual steering, Overall length (mm):3340, Overall width (mm):1650, Overall height (mm):2200, Wheel base (mm):1935, Ground clearance (mm):345, Total weight (kg):1820, Fuel tank capacity (L):55, "Additional features:Bigger fuel tankRear flat face with hitch railsElevated hood, "	37.5/35.8	35.8	2WD	541720
5	Massey Ferguson MF 1035 DI Mahashakthi	Engine HP :39, Make:SIMPSONS S337 T III A, Cylinders:3, Cubic Capacity (cc):2400, Fuel injection pump:Inline, Clutch Type:Dual dry , Transmission ype:Sliding mesh / Partial constant mesh, Number of speeds:8 Forward + 2 Reverse, "Tyres Dimensions:6.00 x 16 Front12.4 x 28 Rear, "Minimum turning circle radius with brakes (mm):2850, PTO Type:Live, six splined shaft, PTO Speed:540 RPM @ 1500 ERPM, "Hydraulics Lifting capacity(Lower links at horizontal position):1100 kgf, Brakes Type:Dry disc brakes (Dura Brakes), Steering Type:Manual steering / Power steering, Overall length (mm):3340, Overall width (mm):1650, Overall height (mm):2210, Wheel base (mm):1785, Ground clearance (mm):345, Total weight (kg):1700, Fuel tank capacity (L):47,	37.5/35.8	35.8	2 WD	486720
6	Massey Ferguson MF 241 DI Mahashakthi	Engine HP :42, Make:SIMPSONS S325.1 TIII A / SIMPSONS S325.1 TIII A FST, Cylinders:3, Cubic Capacity (cc):2500, Fuel injection pump:Inline, Clutch Type:Dual dry , Transmission ype:Partial constant mesh, Number of speeds:8 Forward + 2 Reverse, "Tyres Dimensions:6.00 x 16 Front 12.4 x 28 Rear, "Minimum turning circle radius with brakes (mm):2850, PTO Type:Live, six splined shaft, PTO Speed:540 RPM @ 1500 ERPM, "Hydraulics Lifting capacity(Lower links at horizontal position):1700 kgf, Brakes Type:Sealed Dry Disc Brakes (SDDDB),Steering Type:Manual steering , Overall length (mm):3340, Overall width (mm):1690, Overall height (mm):2200, Wheel base (mm):1785/1935, Ground clearance (mm):345, Total weight (kg):1875, Fuel tank capacity (L):47,	42/38	38	2 WD	554720

Sl.No	Approved Model	Specifications	ENGINE /PTO HP	PTO HP	DRIVE	Sale price including Corporation service charges and GST@12%
7	Massey ferguson MF241 DI Planetary Drive /43HP (PTO 38 HP)	Engine HP :43, Make:SIMPSONS S325.1 TIII A , Cylinders:3, Cubic Capacity (cc):2500, Fuel injection pump:Inline, Clutch Type:Dual dry, Transmission ype:Partial constant mesh, Number of speeds:8 Forward + 2 Reverse, "Tyres Dimensions:6.00 x 16 Front 13.6 x 28 Rear, "Minimum turning circle radius with brakes (mm):2850, PTO Type:Live, six splined shaft, PTO Speed:540 RPM @ 1500 ERPM, Hydraulics Lifting capacity(Lower links at horizontal position):1700 kgf, " Brakes Type:Multi disc oil immersed brakes, Steering Type:Manual steering , Overall length (mm):3338, Overall width (mm):1660, Overall height (mm):2185, Wheel base (mm):1785, Ground clearance (mm):340, Total weight (kg):1900, Fuel tank capacity (L):47, Additional features:PLANETARY DRIVE GEAR BOX,	43/38	38	2 WD	571720
8	MF 241 PM	Engine HP :42.6, Make:SIMPSONS S325.1 TIII A / SIMPSONS S325.1 TIII A FST, Cylinders:3, Cubic Capacity (cc):2500, Fuel injection pump:Inline, Clutch Type:Dual dry , Transmission ype:Partial constant mesh, Number of speeds:8 Forward + 2 Reverse, "Tyres Dimensions:6.00 x 16 Front ,13.6 x 28 Rear, "Minimum turning circle radius with brakes (mm):2850, PTO Type:Live, six splined shaft,PTO Speed:540 RPM @ 1500 ERPM, "Hydraulics Lifting capacity(Lower links at horizontal position):1700 kgf, "Brakes Type:MDSS BRAKES, Steering Type:Manual steering , Overall length (mm):3340, Overall width (mm):1690, Overall height (mm):2200, Wheel base (mm):1785/1935, Ground clearance (mm):345, Total weight (kg):1875, Fuel tank capacity (L):47, Additional features:IN 808 CODE MODEL FST ENGINE AND MDSS BRAKES ARE THERE , ALSO LONGER WHEEL BASE AND FLAT BACK HITCH END IS THERE,	42.6/38.2	38.2	2WD	568720
9	MF241DIPD,,DC,OIB,ELCRTP SPCM	Engine HP :42, Make:SIMPSONS S325.1 TIII A , Cylinders:3, Cubic Capacity (cc):2500, Fuel injection pump:Inline, Clutch Type:Dual dry, Transmission ype:Partial constant mesh, Number of speeds:8 Forward + 2 Reverse, "Tyres Dimensions:6.00 x 16 Front 13.6 x 28 Rear, "Minimum turning circle radius with brakes (mm):2850, PTO Type:Live, six splined shaft, PTO Speed:540 RPM @ 1500 ERPM, Hydraulics Lifting capacity(Lower links at horizontal position):1700 kgf, " Brakes Type:Multi disc oil immersed brakes, Steering Type:Manual steering / Power steering,Overall length (mm):3400, Overall width (mm):1660, Overall height (mm):2200, Wheel base (mm):1785, Ground clearance (mm):345, Total weight (kg):1920, Fuel tank capacity (L):47, Additional features:Asli Side shift Adjustable seat Raised platform Push type pedals	42.6/38.2	38.2	2WD	591720

Sl.No	Approved Model	Specifications	ENGINE /PTO HP	PTO HP	DRIVE	Sale price including Corporation service charges and GST@12%
10	MF5245PD	Engine HP :50, Make:SIMPSONS SJ327 TIII A, Cylinders:3, Cubic Capacity (cc):2700, Fuel injection pump:Inline, Clutch Type:Dual dry, Transmission ype:Partial constant mesh,Number of speeds:8 Forward + 2 Reverse, "Tyres Dimensions:6.00 x 16 Front 14.9 x 28 Rear, "Minimum turning circle radius with brakes (mm):2850, PTO Type:Live, six splined shaft, PTO Speed:540 @ 1790 ERPM, "Hydraulics Lifting capacity(Lower links at horizontal position):1700 kgf, "Brakes Type:Oil immersed brakes, Steering Type:Manual steering, Overall length (mm):3380, Overall width (mm):1715, Overall height (mm):2200, Wheel base (mm):1785, Ground clearance (mm):340, Total weight (kg):2100, Fuel tank capacity (L):47,	49.5/42.4	42.4	2WD	616720
11	MF5245PD SJ327	Engine HP :50, Make:SIMPSONS SJ327 TIII A, Cylinders:3, Cubic Capacity (cc):2700, Fuel injection pump:Inline, Clutch Type:Dual dry, Transmission ype:Partial constant mesh, Number of speeds:8 Forward + 2 Reverse, "Tyres Dimensions:6.00 x 16 Front13.6X28 Rear, " Minimum turning circle radius with brakes (mm):2850, PTO Type:Live, six splined shaft, PTO Speed:540 @ 1790 ERPM, "Hydraulics Lifting capacity(Lower links at horizontal position):1700 kgf, "Brakes Type:Oil immersed brakes, Steering Type:Manual steering, Overall length (mm):3380, Overall width (mm):1715, Overall height (mm):2200, Wheel base (mm):1785, Ground clearance (mm):340, Total weight (kg):2100, Fuel tank capacity (L):47, Additional features:push pedal in 805 code with side air cleaner.	49.5/42.4	42.4	2WD	614720
12	MF5245PD WITH FLAT CH	Engine HP :50, Make:SIMPSONS SJ327 TIII A, Cylinders:3, Cubic Capacity (cc):2700, Fuel injection pump:Inline, Clutch Type:Dual dry, Transmission ype:Partial constant mesh, Number of speeds:8 Forward + 2 Reverse, Tyres Dimensions:6.00 x 16 Front,14.9 x 28 / 13.6 x 28 Rear, "Minimum turning circle radius with brakes (mm):2850, PTO Type:Live, six splined shaft, PTO Speed:540 @ 1790 ERPM, "Hydraulics Lifting capacity(Lower links at horizontal position):1700 kgf, "Brakes Type:Oil immersed brakes, Steering Type:Manual steering, Overall length (mm):3380, Overall width (mm):1715, Overall height (mm):2200, Wheel base (mm):1785,Ground clearance (mm):340, Total weight (kg):2030, Fuel tank capacity (L):47,Additional features:Asli side shift Adjustable seat Rear flat face with hitch rails	49.5/42.4	42.4	2WD	626720

Sl.No	Approved Model	Specifications	ENGINE /PTO HP	PTO HP	DRIVE	Sale price including Corporation service charges and GST@12%
13	MF5245 DI PP 4WD	Engine HP :49, Make:SIMPSONS SJ327 TIII A, Cylinders:3, Cubic Capacity (cc):2700, Fuel injection pump:Inline, Clutch Type:Dual dry, Transmission ype:Partial constant mesh, Number of speeds:8 Forward + 2 Reverse, "Tyres Dimensions:8.3 x 24 Front,14.9 x 28 Rear, " Minimum turning circle radius with brakes (mm):NA, PTO Type:GSPTO, six splined shaft type, PTO Speed:540 @ 1500 ERPM, "Hydraulics Lifting capacity(Lower links at horizontal position):1700 kgf, "Brakes Type:Oil immersed brake, Steering Type:Power steering, Overall length (mm):3365,Overall width (mm):1735, Overall height (mm):1565, Wheel base (mm):1970, Ground clearance (mm):380, Total weight (kg):2450, Fuel tank capacity (L):47,	49.5/42.4	42.4	4WD	780960
14	tractor mf 9000 di tractor with standard accessories hitch draw bar including TR / 45 HP	Engine HP :50, Make:SIMPSONS SJ327 TIII A, Cylinders:3, Cubic Capacity (cc):2700, Fuel injection pump:Inline, Clutch Type:Dual dry, Transmission ype:Comfimesh, Number of speeds:8 Forward + 2 Reverse, "Tyres Dimensions:6.00 x 16 Front14.9 x 28 Rear, Minimum turning circle radius with brakes (mm):3200, PTO Type:Live, single speed PTO, PTO Speed:540 @ 1790 ERPM, "Hydraulics Lifting capacity(Lower links at horizontal position):2050 kgf,Brakes Type:Oil immersed brake, Steering Type:Power steering,Overall length (mm):3595, Overall width (mm):1800, Overall height (mm):2235, Wheel base (mm):1980, Ground clearance (mm):380, Total weight (kg):2140,Fuel tank capacity (L):60, "Additional features:Asli side shift Engine driven auxiliary pump	49.5/45.3	45.3	2 WD	646720
15	tractor mf 9500 di tractor with standard accessories hitch draw bar including TR / 55 HP	Engine HP :58, Make:SIMPSONS TSJ 327 TIII A, Turbo charger,Cylinders:3, Cubic Capacity (cc):2700, Fuel injection pump:Rotary, Clutch Type:Dual, Transmission ype:Comfimesh, Number of speeds:8 Forward + 2 Reverse, "Tyres Dimensions:7.50 x 16 Front,16.9 x 28 Rear, "Minimum turning circle radius with brakes (mm):3250, PTO Type:RPTO, PTO Speed:540 RPM @ 1790 ERPM, "Hydraulics Lifting capacity(Lower links at horizontal position):2050 kgf, "Brakes Type:Oil immersed brake, Steering Type:Power steering,Overall length (mm):3745, Overall width (mm):1878,Overall height (mm):2316, Wheel base (mm):1980, Ground clearance (mm):420, Total weight (kg):2400, Fuel tank capacity (L):60, "Additional features: Asli side shift Engine driven aux. pump, Front weightsAdjustable front axle,Spool valve,	58.0/55.5	55.5	2 WD	716720

Sl.No	Approved Model	Specifications	ENGINE /PTO HP	PTO HP	DRIVE	Sale price including Corporation service charges and GST@12%
16	MF9500 HLC RPTO AND SSV	Engine HP :58, Make:SIMPSONS SJ327E THII A, Cylinders:3, Cubic Capacity (cc):2700, Fuel injection pump:Rotary, Clutch Type:Dual, Transmission ype:Comfimesh, Number of speeds:8 Forward + 8 Reverse, "Tyres Dimensions:7.50 x 16 Front,16.9 x 28 Rear, Minimum turning circle radius with rakes (mm):3420, PTO Type:RPTO, PTO Speed:540 RPM @ 1790 ERPM, "Hydraulics Lifting capacity(Lower links at horizontal position):2050 kgf, Brakes Type:Oil immersed brake,Steering Type:Power steering, Overall length (mm):3745, Overall width (mm):1878,Overall height (mm):2316,Wheel base (mm):1965, Ground clearance (mm):420, Total weight (kg):2360, Fuel tank capacity (L):60, "Additional features:Asli side shift,T 5 Heavy duty front axle axle,Heavy duty clutch,Auxiliary pump,Front weights,Spool valve	58.0/55.5	55.5	2WD	807720
17	MF9500 HLC AND SSV	Engine HP :58, Make:SIMPSONS SJ327E THII A, Cylinders:3, Cubic Capacity (cc):2700, Fuel injection pump:Rotary, Clutch Type:Dual, Transmission T ype:Comfimesh, Number of speeds:8 Forward + 8 Reverse, "Tyres Dimensions:9.50 x 24 Front16.9 x 28 Rear,Minimum turning circle radius with brakes (mm):3485, PTO Type:Live, six splined single speed PTO, PTO Speed:540 RPM @ 1789 ERPM, Hydraulics Lifting capacity(Lower links at horizontal position):2050 kgf, "Brakes Type:Oil immersed brake, Steering Type:Power steering,Overall length (mm):3914, Overall width (mm):185, Overall height (mm):2310, Wheel base (mm):1972, Ground clearance (mm):379 - Front axle, Total weight (kg):2660, Fuel tank capacity (L):60, "Additional features:4 WD,Asli side shift,Auxiliary pump,Front weights,Spool valve	58.0/56.4	56.4	4WD	961960
18	TAFE MF 7250 TRACTOR,	TAFE MF 7250 TRACTOR, ENGINE HP 47, MAKE: SIMPSONS S325 THIIA, 3 CYLINDER, 2500 RPM, DUAL CLUTCH, 8 FORWARD + 2 REVERSE, 6.00 X 16 FRONT, 14.9 X 28 RT TYRES, SIZES: 3545 X 1700 X 2310 X 1930 MM	47		2WD	631379
19	TAFE MF 1035	TAFE MF 1035 SUPER PLUS TRACTOR. ENGINE SIMPSON S337.1 FST, 3 CYLINDER, 2400 CUBIC CAPACITY, DUAL CLUTCH, 8 FORWARD + 2 REVERSE, TYRES:6.0 X 16, 13.6 X 28 ,	41		2 wd	544612
1	Accessories include draw bar, including 3 point linkage, toolkit, and trailer hitch					
2	The basic prices given above are correct if proved wrong the empanelment will be cancelled					
3	If it is found that the rates are furnished above reduced in the regular retail market the empanelment will be cancelled					
4	Final negotiated prices given above are agreed					
	Dealers list	Area of operation				

SI.No	Approved Model	Specifications	ENGINE /PTO HP	PTO HP	DRIVE	Sale price including Corporation service charges and GST@12%
	Sri Lakshmi Auto AgenciesTAFE LTD (ABU) Huzur gardens,Sembium Chennai -600011 Tamilnadu Ph.no -044 66923500S.No:- 138/1, Near wood Complex, NH-5, North Bye Pass Road, Ongole-523002 Mob.no - 9490904222	PRAKASHAM				
	M.G. Brothers Automobiles Pvt. LtdTAFE LTD (ABU) Huzur gardens,Sembium Chennai -600011 Tamilnadu Ph.no -044 66923500NSR Complex,Near Sub Register Office,GNT Road Naidupeta Nellore-524126 Mob.no - 9490904222	NELLORE				
	M.G. Brothers Automobiles Pvt. LtdTAFE LTD (ABU) Huzur gardens,Sembium Chennai -600011 Tamilnadu Ph.no -044 66923500Plot No.B-11, Industrial Estate, A.K.Nagar, Nellore-524004 Mob.no - 9490904222	NELLORE				
	M.G. Brothers Industries Pvt. Ltd.TAFE LTD (ABU) Huzur gardens,Sembium Chennai -600011 Tamilnadu Ph.no -044 6692350015-469,Rajiv Gandhi road, Greams ET,Chittoor-517002 Mob.no - 9490904222	CHITTOOR				

Sl.No	Approved Model	Specifications	ENGINE / PTO HP	PTO HP	DRIVE	Sale price including Corporation service charges and GST@12%
	Vijaya Vasava MotorsTAFE LTD (ABU) Huzur gardens,Sembium Chennai -600011 Tamilnadu Ph.no -044 66923500G.N.T.Road,Eluru-534002 Mob.no - 9490904222	WEST GODAWARI				
	Sri Padmavathi AutomotivesTAFE LTD (ABU) Huzur gardens,Sembium Chennai -600011 Tamilnadu Ph.no -044 66923500Plot No:-3, Block No-3, 4th Phase, AutoNagar, Guntur-522001	GUNTUR				
	PAVAN AUTOMOBILESTAFE LTD (ABU) Huzur gardens,Sembium Chennai -600011 Tamilnadu Ph.no -044 66923500657/2-A, Opp Girls High School, By Pass road, Kadiri-515591	ANANTAPUR				
	M.G.BROTHERS AUTOMOBILES Ltd.,TAFE LTD (ABU) Huzur gardens,Sembium Chennai -600011 Tamilnadu Ph.no -044 66923500Autonagar,Bandar Road-Gudiwada	KRISHNA				

SI.No	Approved Model	Specifications	ENGINE / PTO HP	PTO HP	DRIVE	Sale price including Corporation service charges and GST@12%
	M.G. BROTHERS AUTOMOBILESTAFE LTD (ABU) Huzur gardens,Sembium Chennai -600011 Tamilnadu Ph.no -044 6692350055-1-11, 100Feet Road,Kaleswara building,Near Panta Kalava Bus Stop, Jawahar Auto Nagar, Vijayawada- 520007	KRISHNA				
	SRI RAM ENTERPRISESTAFE LTD (ABU) Huzur gardens,Sembium Chennai -600011 Tamilnadu Ph.no -044 669235009-3-1K, RENIGUNTA ROAD, TIRUPATHI- 517501 Mob.no - 9490904222	CHITTOOR				
	SRI RAGHAVENDRA MOTORSTAFE LTD (ABU) Huzur gardens,Sembium Chennai -600011 Tamilnadu Ph.no -044 66923500VINAYAKA NAGAR,BESIDE VIJAYA DURGA TEMPLE Mob.no - 9490904222	KADAPA				
	K.S.R.TRACTORSTAFE LTD (ABU) Huzur gardens,Sembium Chennai -600011 Tamilnadu Ph.no -044 66923500K.S.R Tractors Survey 176 Kadapa Road, Noonepakalli Nandyal-5018502 Kurnool(Dist)Ph-9985590272 Mob.no - 9490904222	KURNOOL				

Sl.No	Approved Model	Specifications	ENGINE / PTO HP	PTO HP	DRIVE	Sale price including Corporation service charges and GST@12%
	K.S.R.TRACTORSTAFE LTD (ABU) Huzur gardens,Sembium Chennai -600011 Tamilnadu Ph.no -044 66923500MOTIVES,Door No. 2/424/4,mujeeb,complex,B/s Bharat Petrol bunk Yemmiganur,Road Adoni Kurnool Dist AP 518302.	KURNOOL				
	SRI LAKSHMI TRACTORSTAFE LTD (ABU) Huzur gardens,Sembium Chennai -600011 Tamilnadu Ph.no -044 66923500SURVEY NO.81/3,Near Market Yard,Gooty Road, Ananthapuramu-515001. land line no.08554-222884.	ANANTHAPUR				
	Maha Lakshmi Auto Ventures, Plot No: 51- Sarpavaram,APIIC Auto nagar,Kakinada-East Godavari-533005 Mob.no - 9490904222	EAST GODAWARI				
	sri sai durga motors, peddapadu road, srikakulam	srikakulam				
	Annapurna tractors,plot no.C25, RSNO.219,300, BUNDER ROAD, Gudivada , krishna	krishna				
	sri suryambica auto mobiles, near aruna jute mill Y junction , Vizianagaram	Vizianagaram				
	Tirumala tafe tractors , piduguralla , guntur	guntur				